

# DA-65EF Monoblock



## Specification

Thermal efficiency	
U <sub>w</sub> *: Coefficient value for reference design	1,3 W/m <sup>2</sup> K
U factor*:	0,23* Btu/h·ft <sup>2</sup> ·F
*:	Reference window with dimensions of 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name:	DA-65EF
Installation depth:	Frame 65 mm   Sash 74 mm   Monoblock option: 100mm, 120mm, 140mm, 160mm
Number of chambers:	3
Thermal break:	30 mm thick glass-fibre reinforced polyamide
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	4/18/4/18/4
U <sub>g</sub> value:	0,5 W/m <sup>2</sup> K
Glazing Package Thickness:	Glazing thickness available from 13 to 60 mm
Sound insulation of available glazing:	R <sub>w</sub> : from 31 to 47 dB
Fittings	
Type:	---
Hinges:	surface
Anti-theft protection:	anti-theft catches
Microventilation:	yes
Other:	Four-stage tilt and slide mechanism   Handle rotation lock with a lifter
Handle	
Colors:	---
Handle model:	1006

## Dimensions

Maximum window width - single sash:	1600 mm
Maximum window height - single sash:	2400 mm
Maximum window width - double sash with a movable post:	3200 mm
Maximum window height - double sash with a movable post:	2400 mm
Maximum sash area:	3 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m <sup>2</sup> and weight of 250 kg):	3500 x 2900 mm lub 2900 x 3500 mm