

DA-90 Thermo corner option



Specification

Thermal efficiency	
U _w *: Coefficient value for reference design	0,80 W/m ² K
U factor*:	0,14* Btu/h·ft ² ·F
*:	Reference window with dimensions: 2 x 48 7/16in x 58 4/16in (2x 1230 mm x 1480 mm) with standard glass 4X18x4x18x4
Profile	
Profile name:	DA-90 Thermo
Installation depth:	Sash: 99 mm Frame: 90 mm
Number of chambers:	3
Thermal break:	45 mm glass-fibre reinforced polyamide, insulation insert in middle chamber
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	4X18x4x18x4
U _g value:	0,5 W/m ² K

Glazing Package Thickness:	from 21 to 67 mm
Sound insulation of available glazing:	Rw: from 31 to 47 dB
Fittings	
Type:	n/a
Hinges:	n/a
Anti-theft protection:	n/a
Microventilation:	n/a
Other:	handle rotation lock with a lifter
Handle	
Colors:	---
Handle model:	1006
Sash size	
Min. sash width:	560 mm x 560 mm x 560 mm
Max. sash width:	2400 mm x 3000 mm x 3000 mm
Min. sash height:	560 mm x 560 mm x 560 mm
Max. sash height:	2400 mm x 3000 mm x 3000 mm
Max. sash weight:	---
Max. sash area:	---

Photos

