

# DA-77 HST



## Specification

Thermal efficiency	
U <sub>w</sub> *: Coefficient value for reference design	1,1 W/m <sup>2</sup> K
U factor*:	---
*:	---
Profile	
Profile name:	DA-77
Installation depth:	Sash: 77 mm   Frame: 174 mm
Number of chambers:	3
Thermal break:	35 mm glass-fibre reinforced polyamide thermal breaks
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	Triple glazing package 4x18x4x18x4
U <sub>g</sub> value:	0,5 W/m <sup>2</sup> K
Glazing Package Thickness:	glazing thickness available: from 14 to 58 mm
Sound insulation of available glazing:	w: from 31 to 47 dB
Fittings	
Type:	Lift - sliding fitting

Hinges:	n/a
Anti-theft protection:	n/a
Microventilation:	yes
Other:	n/a
<b>Handle</b>	
Colors:	---
Handle model:	Made of aluminum
<b>Maximum construction dimensions</b>	
Width:	6500 mm
Height:	3000 mm
<b>Sash size</b>	
Min. sash width:	900 mm
Max. sash width:	3300 mm
Min. sash height:	1900 mm
Max. sash height:	3200 mm
Max. sash weight:	300 kg
Max. sash area:	---
<b>Other</b>	
Other:	OPTION: Automatic doors - opening and closing with remote control

## Photos

