

# Profiled doors DA-77



## Specification

| Thermal efficiency  |  |
|---|--|
| U <sub>w</sub> *:<br>Coefficient value for reference design | 1,2 W/m <sup>2</sup> K   |
| U factor*:  | ---  |
| *:  | doors reference 1230 mm x 2180 mm  |
| Profile   |  |
| Profile name:   | DA-77  |
| Installation depth:   | Sash: 77 mm   Frame: 77 mm   |
| Number of chambers:   | 4  |
| Thermal break:  | 31 mm glass-fibre reinforced polyamide thermal breaks  |
| Number of seals:  | Two EPDM dual-component synthetic rubber seals   |
| Glass   |  |
| Glazing package:  | Triple glazing package 33,1x18x4x18x33,1   |
| U <sub>g</sub> value:                                       | 0,5 W/m <sup>2</sup> K   |
| Glazing Package Thickness:                                  | glazing thickness available: from 14 to 58 mm  |
| Sound insulation of available glazing:                      | ---  |
| Fittings  |  |
| Type:   | ---  |
| Hinges:   | SURFACE HINGES Durable and stable hinges adjustable in three planes. They guarantee smooth door operation and increase safety. Standard color: white, brown, silver   Optional colors: Joinery color |
| Anti-theft protection:                                      | ---  |
| Microventilation:   | ---  |
| Other:  | ---  |
| Handle  |  |
| Colors:   | Standard color: white, brown, silver   |
| Handle model:   | Handle on a long backplate made of high quality aluminum.  |

**Insert**

|              |                     |
|--------------|---------------------|
| Insert type: | Construction insert |
|--------------|---------------------|

**Lock**

|            |  |
|------------|--|
| Lock type: | 1-point locking system with a classic latch-bolt mechanism |
|------------|--|

**Sash size**

|                   |         |
|-------------------|---------|
| Min. sash width:  | 900 mm  |
| Max. sash width:  | 1400 mm |
| Min. sash height: | 2050 mm |
| Max. sash height: | 3000 mm |
| Max. sash weight: | 180 kg  |
| Max. sash area:   | ---     |