

DPP-70 LumiaLine



Specification

Thermal efficiency	
U _w *: Coefficient value for reference design	0,96 W/m ² K
U factor*:	0,17 Btu/h·ft ² ·F
*:	Glass: 4/14/4/14/4; gas: argon; warm edge; window size 48 7/16in x 58 4/16in (1230mm x 1480mm)
Profile	
Profile name:	DPP-70 LumiaLine
Installation depth:	70 mm
Number of chambers:	5
Thermal break:	none
Number of seals:	2
Glass	
Glazing package:	4/14/4/14/4/
U _g value:	0,6 W/m ² K
Glazing Package Thickness:	40 mm
Sound insulation of available glazing:	---
Fittings	

Type:	---
Hinges:	surface
Anti-theft protection:	2 Anti-theft catches
Microventilation:	optional
Other:	---
Handle	
Colors:	---
Handle model:	1006
Dimensions	
Maximum window width - single sash:	1270 mm
Maximum window height - single sash:	2575 mm
Maximum window width - double sash with a movable post:	1850 mm
Maximum window height - double sash with a movable post:	2575 mm
Maximum sash area:	2,19 m ²
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m ² and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm