

# DPQ-82 thermoSecure



## Specification

Thermal efficiency	
Uw*: Coefficient value for reference design	0,75 W/m <sup>2</sup> K
U factor*:	0,13* Btu/h·ft <sup>2</sup> ·F
*:	Glass 4/18/4/18/4 ECLAZ. gas: argon, warm edge spacer, window size 48 7/16in x 58 4/16in (1230mm x 1480mm)
Profile	
Profile name:	DPQ-82 thermoSecure
Installation depth:	82 mm
Number of chambers:	7
Thermal break:	2
Number of seals:	3
Glass	
Glazing package:	4Eclaz /18/4/18/4Eclaz
Ug value:	0,5 W/m <sup>2</sup> K
Glazing Package Thickness:	48 mm

Sound insulation of available glazing:	---
<b>Fittings</b>	
Type:	---
Hinges:	surface
Anti-theft protection:	2 Anti-theft catches
Microventilation:	yes
Other:	---
<b>Handle</b>	
Colors:	---
Handle model:	Secuforte Hamburg
<b>Dimensions</b>	
Maximum window width - single sash:	1500 mm
Maximum window height - single sash:	2575 mm
Maximum window width - double sash with a movable post:	2085 mm
Maximum window height - double sash with a movable post:	2480 mm
Maximum sash area:	2,25 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg):	3500 x 2900 mm lub 2900 x 3500 mm

## Photos

