



Specification

| Thermal efficiency | |
|---|---|
| U _w *: Coefficient value for reference design | 1,2 W/m ² K |
| U factor*: | 0.21* Btu/h·ft ² ·F |
| *: | Glass: 4/16/4; gas: argon; warm edge spacer; window size: 48 7/16in x 58 4/16in (1230 mm x 1480 mm) |
| Profile | |
| Profile name: | DDF-68 |
| Installation depth: | 68 mm |
| Number of chambers: | n/a |
| Thermal break: | n/a |
| Number of seals: | 3 |
| Glass | |
| Glazing package: | 4/16/4 |
| U _g value: | 1,0 W/m ² K |
| Glazing Package Thickness: | 24 mm |

| | |
|---|------------------------------------|
| Sound insulation of available glazing: | --- |
| Fittings | |
| Type: | --- |
| Hinges: | surface |
| Anti-theft protection: | 1 anti-theft catches RU |
| Microventilation: | tak |
| Other: | handle rotation lock with a lifter |
| Handle | |
| Colors: | --- |
| Handle model: | 1006 |
| Dimensions | |
| Maximum window width - single sash: | 1500 mm |
| Maximum window height - single sash: | 2600 mm |
| Maximum window width - double sash with a movable post: | 1800 mm |
| Maximum window height - double sash with a movable post: | 2600 mm |
| Maximum sash area: | 3 m ² |
| Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg): | 3500 x 2900 mm or 2900 x 3500 mm |

Photos

