



Specification

Thermal efficiency	
U _w *: Coefficient value for reference design	0,89 W/m ² K
U factor*:	0,16* Btu/h·ft ² ·F
*:	Glass: 4/14/4/14/4; gas: argon, warm edge spacer; window size: 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name:	DDR-78
Installation depth:	78 mm
Number of chambers:	n/a
Thermal break:	n/a
Number of seals:	3
Glass	
Glazing package:	4/14/4/14/4
U _g value:	0,6 W/m ² K

Glazing Package Thickness:	40 mm
Sound insulation of available glazing:	---
Fittings	
Type:	---
Hinges:	surface
Anti-theft protection:	1 anti-theft catches RU
Microventilation:	tak
Other:	handle rotation lock with a lifter
Handle	
Colors:	---
Handle model:	1006
Dimensions	
Maximum window width - single sash:	1500 mm
Maximum window height - single sash:	2525 mm
Maximum window width - double sash with a movable post:	2080 mm
Maximum window height - double sash with a movable post:	2525 mm
Maximum sash area:	3 m ²
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm

Photos

